YONGNUO LED Stick Light

YONGNUO
www.hkyongnuo.com



YONGNUO LED Stick Light		YN360IV	YN660S	YN660LED	YN100Soft Soft Stick Light	YN60Soft Soft Stick Light	YN30Soft Soft Stick Light	YN360 Mini	YN360III PRO	YN360III	YN360	YN360 II	YN360S
Light Source	LED Lamp beads	400	672	672	480	320	160	180	360	360	320	320	140
	RGB SMD LEDs	80	——	120	140	96	48	60	60	60	40	40	——
Color Rendering Index		⩾96	⩾96	⩾96	⩾95	⩾95	⩾95	⩾95	⩾96	⩾95	⩾95		
Distance0.5m Lumen Value		5600K 6494 Lux R: 1124 Lux G: 2140 Lux B: 534 Lux	3200K 7300 Lux 4000K 12784 Lux 5600K 8852Lux	5600K 8647 Lux R: 1246 Lux G: 2599 Lux B: 698 Lux	7000K 2236 Lux R: 999 Lux G: 1950 Lux B: 452 Lux	7000K 1978 Lux R: 554 Lux G: 1696 Lux B: 404 Lux	4000K 1032 Lux R: 326 Lux G: 809 Lux B: 329 Lux	LED: 2057 Lux RGB: 1517 Lux	White: 2880 Lux Bi-color: 2790 Lux RGB: 1970 Lux	White: 2880 Lux Bi-color: 2790 Lux RGB: 494 Lux	White: 2560 Lux Bi-color: 2480 Lux RGB: 494 Lux	White: 2560 Lux Bi-color: 2480 Lux RGB: 494 Lux	White: 1480 Lux Bi-color: 1406 Lux
Power		24w	60w	45w	LED: 30w RGB: 30w	LED: 20w RGB: 20w	LED: 10w RGB: 10w	LED: 10w RGB: 10w	21.6w & 20w	21.6w & 10.8w	19.2w & 10.8w	19w & 8w	15w
Built-in Light Adjustment Curves		Exponential Function Sine Function Logarithmic Function Linear Function	——	——	——	——	——	——	——	——	——	——	——
Optional Color Temperature		Reddish and greenish adjustment Bi-color: 2000K-10000K+RGB	Bi-color: 3200K-5600K	Reddish and greenish adjustment Bi-color: 2000K-9900K+RGB	Reddish and greenish adjustment Bi-color: 2000K-10000K+RGB	Reddish and greenish adjustment Bi-color: 2000K-10000K+RGB	Reddish and greenish adjustment Bi-color: 2000K-10000K+RGB	Bi-color: 2700K-7500K+RGB	White: 5600K+RGB Bi-color: 3200K-5600K+RGB				White: 5600K Bi-color: 3200K-5600K
APP Bluetooth Remote Control		√ FX 31 √ Equipped with touch screen remote control	√ FX11	√ FX 31	√ FX 31	√ FX 31	√ FX 31	√ FX 31	√ FX 10 √ Equipped with touch screen remote control		√	√	√
Built-in Battery		X	X	X	√ Discharge time white /yellow light: about 80 Minutes	√ Discharge time white /yellow light: about 123 Minutes	√ Discharge time white /yellow light: about 142 Minutes	√	X		X	√ with built-in 7.2V/2600m electricity core*1	X
Power Supply Mode		① NP-F series lithium battery or external DC power supply	① NP-F series lithium battery or external DC power supply	① NP-F series lithium battery or external DC power supply	Built-in lithium battery or external power supply	Built-in lithium battery or external power supply	Built-in lithium battery or external power supply	Built-in lithium battery or external power supply	① NP-F series lithium battery or external DC power supply			Built-in lithium battery or external power supply	① NP-F series lithium battery or external DC power supply
External DC Power Supply		DC 12V2A	12V5A	12V5A	DC 19V3A	DC 12V2A	USB Type-C 5-15V2A	Type-C 9-15V2A	12V2A		12V2A	12V2A	12V2A
Package Size		570*60*95mm	820*150*105mm	820*150*105mm	1090*130*110mm	680*130*110mm	350*70*70mm	350*70*70mm	590*70*70mm		583*48*24mm	585*115*50mm	465*64*35mm
Weight		794g	1430g	2400g	1375g	725g	420g	660g	805g		489g	1134g	320g
Lighting Angle		110° & 55°	55°	110° & 55°	110°	110°	110°	110°	110° & 55°		110° & 55°	110° & 55°	110°
Contents		Video light,Reflector, Screws(4), Remote control, Storage bag, User manual, Product certification	Video light, User manual, Storage bag	Video light, Grille, Soft light cloth, User manual, Storage bag	Video light, Tube clip,Grate, Storage bag, Power adapter, Bracket	Video light, Tube clip,Grate, Storage bag, Power adapter, Bracket	Video light, Grate, Storage bag, USB cable, Iron sheet(2), Lanyard, After-sales card	Video light, Grille,Lightsphere, Storage bag, Charging cable, Lanyard, After-sales card, 3M adhesive magnetic sheet	Video light, Color temperature plate, Storage bags, Remote control, Lanyard, User manual		Video light, Color temperature plate, Storage bag, User manual	Video light, Power adapter, Storage bag, User manual	Video light, User manual

① NP-F Series Lithium battery; ② The video light cannot be turned on simultaneously while using the micro USB interface power cable to charge the smart devices.

③ FX10: with 10 special scene fill light modes; FX11: with 11 special scene fill light modes; ④ FX31: with 31 special scene fill light modes.